



FEATURES



- 2.07 Mega pixels Full HD SONY CMOS Color camera
- 1/2.8" Color CMOS high resolution image sensor (STARVIS)
- HD-TVI 1080p 30fps
- IP69K Waterproof Rating
- Diagonal 154°, 140° or 66° Viewing angle
- Normal/Mirror Image adjustable (via loop wire)
- Ultra low light performance
- Automatic Electronic Iris
- Built-in Microphone (for one-way Audio)
- Multi purpose (Frontview, Sideview, Rearview, Surveillance, etc)
- Temperature Range -40°C to +80°C
- Vibration resistant (10G)
- Waterproof screw type connector, 4-pin mini-DIN
- ECE R10.05 approved (EMC)

Available versions of model MXN44C-TVI:

MXN44C-078-TVI Viewing angle: 66°(D) x 58°(H) x 32°(V)

MXN44C-140-TVI Viewing angle: 140°(D) x 124°(H) x 67°(V)

MXN44C-160-TVI Viewing angle: 154°(D) x 133°(H) x 93°(V)

Specifications

| | |
|-----------------------|---|
| Image Sensor | 1/2.8" SONY CMOS Sensor (STARVIS) |
| Effective Pixels | 2.07 Mega pixels 1920(H) X 1080(V) |
| Resolution | 1080 TV lines |
| Scanning System | Progressive |
| Video Output | HD-TVI 4.0, 1080P/30fps |
| Audio Input | High Sensitive C-Microphone |
| S/N ratio | Minimum 48dB (at AGC off) |
| Minimum illumination | 0.5 Lux (50IRE) |
| Power consumption | DC 12V, 100mA |
| Power range | DC 9 ~ 48V |
| Operating temperature | -40°C to +80°C |
| Viewing angle | 140°(Diagonal) x 124°(Horizontal) x 67°(Vertical) |
| Dimensions | Ø38mm, 59(W) x 38(D) x 50(H) incl. bracket |
| Weight | Approx. 107g (total weight incl. bracket : 120g) |